



# AT10.1 SERIES BATTERY CHARGER ORDERING WORKSHEET

JF5021-02

## Customer Information

Customer Purchase Order		Battery Type	
Quote Number		# of Cells	
Contact Name		Float Voltage Setting	Vdc
Contact Phone Number		Equalize Voltage Setting	Vdc

## AT10.1 Battery Charger Factory Ordering Code (standard specifications) Group II (30-100 Adc Output)

<b>AT10</b>																
A	B	C	D	E	F	G	H	J	K	L	M	N	P			

DESCRIPTION	CODE	FEATURE
<b>A</b> SERIES	AT10	AT10.1 CHARGER
<b>B</b> NOMINAL DC OUTPUT VOLTAGE	012	12 Vdc
	024	24 Vdc
	048	48 Vdc
	130	130 Vdc
<b>C</b> NOMINAL DC OUTPUT CURRENT	030	30 Adc
	040	40 Adc
	050	50 Adc
	075	75 Adc
<b>D</b> FILTERING	U	UNFILTERED
	F	FILTERED
	E	ELIMINATOR
<b>E</b> AC INPUT VOLTAGE	120	120 Vac 60Hz
	208	208 Vac 60Hz
	240	240 Vac 60Hz
	480	480 Vac 60Hz
	220	220 Vac 50/60 Hz
	380	380 Vac 50/60 Hz
	416	416 Vac 50/60 Hz

DESCRIPTION	CODE	FEATURE
<b>F</b> AC CIRCUIT BREAKER RATING (SEE TABLE)	S	STANDARD
	M	MEDIUM AIC
	H	HIGH AIC
	0	NO AC BREAKER
<b>G</b> AC FUSES (200 KAIC)	F	SUPPLIED
	X	NOT SUPPLIED
<b>H</b> DC CIRCUIT BREAKER RATING (SEE TABLE)	S	STANDARD
	M	MEDIUM AIC
	H	HIGH AIC
	0	NO DC BREAKER
<b>J</b> DC FUSES (20 KAIC)	A	SUPPLIED
	X	NOT SUPPLIED
<b>K</b> AUXILIARY ALARM RELAY BOARD	A	SUPPLIED
	X	NOT SUPPLIED
<b>L</b> GROUND PAD	G	SUPPLIED
	X	NOT SUPPLIED
<b>M</b> LIGHTNING ARRESTOR	L	SUPPLIED
	X	NOT SUPPLIED
<b>N</b> FUNGUS PROOFING	F	INCLUDED
	X	NOT INCLUDED
<b>P</b> STATIC PROOFING	S	INCLUDED
	X	NOT INCLUDED

## AT10.1 Options - Group II (30-100 Adc Output)

<input type="checkbox"/>	EI0191-0X	Enclosure drip shield assembly	<input type="checkbox"/>	EI5036-0X	Style-5017 NEMA-4/12/13 type enclosure
<input type="checkbox"/>	EI0192-02	60in floor mounting brackets	<input type="checkbox"/>	EI5037-0X	Style-5018 NEMA-4/12/13 type enclosure
<input type="checkbox"/>	EI0193-01	19in rack mounting brackets	<input type="checkbox"/>	EJ5033-0X	External temperature compensation probe <input type="text"/> length
<input type="checkbox"/>	EI0193-0X	23in rack mounting brackets	<input type="checkbox"/>	EJ5088-0X	Ground detection dc voltmeter w/switch
<input type="checkbox"/>	EI5008-00	Wall mounting brackets	<input type="checkbox"/>	EJ5037-0X	DNP3 Level 2 / Modbus communications module
<input type="checkbox"/>	EJ5041-0X	Cabinet heater assembly	<input type="checkbox"/>	PM5005-00	Compatible modem option for communications module
<input type="checkbox"/>	EI5038-0X	Padlock for front panel	<input type="checkbox"/>	EH5026-0X	Modem cable <input type="text"/> length

## Additional Features / Customer Notes

## Input / Output Circuit Breaker Ampere Interrupting Ratings Table

CODE	TYPE	AC RATINGS (ALL INPUT VOLTAGES)	DC RATINGS (125 Vdc)	DC RATINGS (250 Vdc)
S	STANDARD AIC	5,000 AIC	5,000 AIC	-
M	MEDIUM AIC	25,000 AIC	10,000 AIC	10,000 AIC
H	HIGH AIC	65,000 AIC	25,000 AIC	25,000 AIC