



NOTES:

- 1) ENCLOSURE IS A NEMA-1 TYPE CABINET WITHOUT GASKETS.
- 2) ALLOW 6in (152mm) OF FREE AIR (TOP AND FRONT OF CABINET) FOR VENTILATION.
- 3) FOUR (4) KEY-HOLE SLOTS ARE PROVIDED ON THE BACK OF ENCLOSURE AS SHOWN, FOR WALL-MOUNTING WITH .25in (6.25mm) HARDWARE.
- 4) FOUR (4) 1.31in/33mm DIA KNOCKOUTS ARE PROVIDED AS SHOWN, WITH TWO (2) ADDITIONAL KNOCKOUTS FEATURED ON BOTTOM PANEL OF ENCLOSURE. USE OF ANY OF THESE FOUR (4) LOWER CONDUIT KNOCKOUTS WILL ALLOW REMOVAL OF THE CABINET SHROUD WITHOUT REMOVAL OF EXTERNAL WIRING.
- 5) BATTERY CHARGER SHIPPING WEIGHT RANGE: APPROXIMATELY 44-20 lbs. / 80-36 kg.
- 6) STANDARD CIRCUIT BREAKER LOCATION AT BOTTOM OF ENCLOSURE. 480VAC AND/OR MEDIUM/HIGH AIC CIRCUIT BREAKERS RELOCATED TO TOP PENTHOUSE ENCLOSURE.

DUAL DIMENSIONS in mm

				THIRD ANGLE PROJECTION		Hindle Power 1075 Saint John Street Easton, PA 18042-6661 PH 610-330-9000 FAX 610-330-8510 www.hindlepowerinc.com	
				DRAWN BY MCR APPROVED	022603	TITLE AT10.1 SERIES BATTERY CHARGER OUTLINE: NEMA-1 STYLE-586 ENCLOSURE W/PENTHOUSE	
				UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:		DRAWING No JE5023-01 REV 0 B	
0	E1151	022603		SCALE NTS	PART No JE5023-01	SHEET 1 OF 1	